

LK953ST DLP® Laser Projector

LK953ST Features

- High Brightness with 5000 Lumens with High Contrast and Readability
- Blue Core Laser Technology for 20,000 Hours of Life
- IP5X Certified Dust Proof Sealed Engine Eliminates the Need for Filter Cleaning
- Short Throw Projection – with 0.81 ~ 0.88 throw ratio
- Big Zoom for diverse mounting options
- Vertical and Horizontal Lens Shift for Flexible Installation
- 360° rotation projection
- Separate HDBaseT and Networking Connections



Connectivity

- Wired Remote In
- RS232 In (D-sub 9pin, male)
- USB TypeB (Service)
- USB TypeA (5V/2A power)
- LAN Port (RJ45 for Network control)
- HDBaseT
- HDMI In (HDCP2.2)
- HDMI In
- HDMI Out
- PC In
- Monitor out (D-sub 15pin, Female)
- Audio in (mini jack)
- Audio out (mini jack)
- 12V Trigger
- IR Receiver (Front)
- IR Receiver (Rear)
- Kensington anti-theft lock slot

SPECIFICATIONS		LK953ST
DISPLAY	Projection System	DLP® Single 0.47" XPR 4K
	DMD type	DC3 DMD Chip
	Native Resolution	4K UHD (3840 x 2160)
	Brightness	5000 ANSI Lumens
	Contrast Ratio*	100,000:1
	Display Color	30 Bits (1.07 billion colors)
	Aspect Ratio	Native 16:9 (5 aspect ratio selectable)
	Light Source	Laser
	Light Source life*	20,000 hrs
OPTICAL	Throw Ratio	0.81 ~ 0.88
	Zoom Ratio	1.1x
	Lens Control	Manual Zoom and Focus
	Lens shift	Manual lens shift, V: ±60 %; H: ±23 %
	Keystone Correction	1D keystone, V: ±30 degree
	Projection Offset	NA
	Projection Size	30" ~ 300"
AUDIO	Built-in Speaker	10W
SPECIAL FEATURE	Security (anti-theft)	Security Bar
	Feature	4K UHD, HDR10, Projector/ Remote Control ID Setting, Auto High Altitude Mode, HDBaseT, LAN Control, 360° Projection, Dust-Proof Filter
COMPATIBILITY	Resolution Support	Up to 3840x2160p
	Horizontal Frequency	15K ~135KHz
	Vertical Scan Rate	24~120Hz
	HDTV Compatibility	SDTV(480i/576i), EDTV (480p/576p, HDTV (720p, 1080i 60/50, 1080P 50/60/30/25/24, 3840x2160p 60/50/30/25/24)
	Video Compatibility	NA
POWER	Power Consumptions (Max/Normal/Eco)	Max 585W/ Normal 520W/ Eco 390W
	Standby Power consumption	Normal < 0.5W, Network <2W
	Power Supply	100 ~ 240V AC
DIMENSION AND WEIGHT	Product Dimensions (WxHxD)	490.0x159.0 x 380.0mm
	Product Weight	10.1 kg
OPERATION CONDITION	Noise Level (Normal/Eco)	40/38 dBA
	Operating Temperature*	0 ~ 40°C
OSD	On-Screen Display Languages	Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian /Persian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnam (30 languages)
ACCESSORIES	STANDARD	OPTIONAL
	Power Cord Remote control (RCA011) Lens cover AAA Batteryx2 Installation Guide/Regulatory Statement (Combined) Warranty card(by sku) Anti-dust Filter	Ceiling mount (CMG3)

ENVIRONMENT NOTICE

* LightSource life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

* The Contrast is measure by Full On Full Off standard.



- Wired Remote In
- RS232 In (D-sub 9pin, male)
- USB TypeB (Service)
- USB TypeA (5V/2A power)
- LAN Port (RJ45 for Network control)
- HDBaseT
- HDMI In (HDCP2.2)
- HDMI In
- HDMI Out
- PC In
- Monitor out (D-sub 15pin, Female)
- Audio in (mini jack)
- Audio out (mini jack)
- 12V Trigger
- IR Receiver(Front)
- IR Receiver (Rear)
- Kensington anti-theft lock slot

BenQ America Corp.
www.BenQ.us

BenQ is a registered trademark of BenQ Corp. All rights reserved. Product names, logos, brands and other trademarks featured or referred to in this material are the property of their respective trademark holders. Specifications subject to change without notice.



Because it matters