

265-LS

Details & Specifications

IN-WALL 3-WAY SPEAKER

Lower and Upper -3dB Limits : 41 Hz → 29,000 Hz

Nominal Impedance: 8 ohms

Sensitivity (1 watt @ 1 meter): 91 dB

Total Frequency Response: 28 Hz → 33,000 Hz

Availability: Internationally

Depth: 3.75" (9.53 cm)

Driver Complement:

(1) 1" (2.54 cm) d (Round) Dynamic Balance ring radiat Tweeter

(2) 6.5" (16.51 cm) d (Round) Dynamic Balance aerated polypropylene cone and rubber surround - Mid/Woofer

Driver Enclosure Type: Power Port Bass Vented

Height: 20.875" (53.02 cm)

Orientation: Horizontal

Qty Included: 1

Weight: 9 lbs (4.08 kg)

Width: 8.875" (22.54 cm)

Recommended Amplifier Power Per Channel: 10 watts → 200 watts

Audio Inputs

-

Speaker Inputs: (1) Pair of Spring-loaded binding posts - Gold-plated

Dimensions: 19.188" (48.74 cm) h x 7.25" (18.42 cm) w

Flush Mounting Depth: 3" (7.62 cm) -

Shape: Rectangle

OVERALL

Optional Accessories: (1) PB LC265i Pre-Construction Bracket - Sold Separately

Total Pieces: 1