

V80 IN-CEILING SPEAKER



Qty Included	1
Depth	4.125" (10.48 cm)
Driver Complement	<ul style="list-style-type: none">• (1) 8" (20.32 cm) d (Round) Composite Polymer Cone with Butyl Rubber Surround - Mid/Woofer• (1) 1" (2.54 cm) d (Round) Swivel Mount, Silk Dome - Tweeter
Grille Dimensions	11.125" (28.26 cm) diameter
Shape	Round
Dimensions	9.375" (23.81 cm) diameter
Flush Mounting Depth	3.625" (9.21 cm) -
Total Frequency Response	30 Hz → 27,000 Hz
Nominal Impedance	8 ohms
Sensitivity (1 watt @ 1 meter)	90 dB
Lower and Upper -3dB Limits	45 Hz → 25,000 Hz
Recommended Amplifier Power Per Channel	10 watts → 100 watts
Audio Inputs	-
Speaker Inputs	(1) Pair of Push Connectors - Gold Plated
Total Pieces	1
Included Accessories	<ul style="list-style-type: none">• (1) Polk's Wafer-thin Sheer Grille™ - White, Paintable
Optional Accessories	<ul style="list-style-type: none">• (1) PB LC80I - Pre-Construction Bracket - Sold Separate• (1) Fire-Rated Back Box - Sold Separate• (1) Square Sheer Grille™ - White, Paintable - Sold Separate
Carton 1	6.5" (16.51 cm) h x 12.25" (31.12 cm) w x 12.5" (31.75 cm) d - 5 lbs (2.27 kg)