

# Polk Audio V60 In Ceiling

## IN-CEILING SPEAKER



Lower and Upper -3dB Limits	50 Hz → 25 Hz
Nominal Impedance	8 ohms
Sensitivity (1 watt @ 1 meter)	89 dB
Total Frequency Response	33 Hz → 27 Hz
Depth	3.75" (9.53 cm)
Driver Complement	<ul style="list-style-type: none"><li>• (1) 6.5" (16.51 cm) d (Round) Composite Polymer Cone with Butyl Rubber Surround - Mid/Woofer</li><li>• (1) 0.75" (1.91 cm) d (Round) Swivel Mount, Silk Dome - Tweeter</li></ul>
Grille Dimensions	9.625" (24.45 cm) diameter
Qty Included	1
Recommended Amplifier Power Per Channel	10 watts → 100 watts
Dimensions	8.188" (20.8 cm) diameter
Flush Mounting Depth	3.25" (8.26 cm) -
Shape	Round
Audio Inputs	-
Speaker Inputs	(1) Pair of Push Connectors - Gold Plated

## OVERALL



Included Accessories	<ul style="list-style-type: none"><li>• (1) Polk's Wafer-thin Sheer Grille™ - White, Paintable</li></ul>
Optional Accessories	<ul style="list-style-type: none"><li>• (1) PB LC60I - Pre-Construction Bracket - Sold Separate</li><li>• (1) Fire-Rated Back Box - Sold Separate</li><li>• (1) Square Sheer Grille™ - Sold Separate</li></ul>
Total Pieces	1
Carton 1	6.25" (15.88 cm) h x 10.75" (27.31 cm) w x 11" (27.94 cm) d - 4 lbs (1.81 kg)

## WARRANTY



Lifetime Warranty	Yes
-------------------	-----