

Polk Audio V6S in Ceiling

OVERALL

Total Pieces	1
Included Accessories	<ul style="list-style-type: none">• (1) Polk's Wafer-thin Sheer Grille™ - White, Paintable
Optional Accessories	<ul style="list-style-type: none">• (1) PB LC60I - Pre-Construction Bracket - Sold Separate• (1) Fire-Rated Back Box - Sold Separate• (1) Square Sheer Grille™ - White, Paintable - Sold Separate
Carton 1	5.75" (14.61 cm) h x 11" (27.94 cm) w x 23.25" (59.06 cm) d - 12 lbs (5.44 kg)

IN-CEILING SPEAKER

Qty Included	1
Depth	3.75" (9.53 cm)
Driver Complement	<ul style="list-style-type: none">• (1) 6.5" (16.51 cm) d (Round) Composite Polymer Cone with Butyl Rubber Surround - Mid/Woofer• (2) 0.75" (1.91 cm) d (Round) Swivel Mount, Silk Dome - Tweeter
Grille Dimensions	9.625" (24.45 cm) diameter
Shape	Round
Dimensions	8.188" (20.8 cm) diameter
Flush Mounting Depth	3.25" (8.26 cm) -
Total Frequency Response	33 Hz → 27,000 Hz
Nominal Impedance	8 ohms
Sensitivity (1 watt @ 1 meter)	89 dB
Lower and Upper -3dB Limits	50 Hz → 25,000 Hz
Audio Inputs	
Speaker Inputs	(1) Pair of Push Connectors - Gold Plated

EXTERNAL AMPLIFIER RECOMMENDED POWER PER CHANNEL

Stereo	Min: 10W / Max: 100W
Surround Sound	Min: 10W / Max: 200W