

polk audio VS80 F/X-LS

OVERALL



Total Pieces	1
Included Accessories	<ul style="list-style-type: none">• (1) Polk's Wafer-thin Sheer Grille™ - White, Paintable
Optional Accessories	<ul style="list-style-type: none">• (1) PB LC80I - Pre-Construction Bracket - Sold Separate
Carton 1	7.5" (19.05 cm) h x 12.75" (32.39 cm) w x 25.25" (64.14 cm) d - 11.5 lbs (5.22 kg)

WARRANTY



Lifetime Warranty	Yes
-------------------	-----

IN CEILING LOUDSPEAKER



Qty Included	Pair
Availability	US Internationally
Depth	5.13" (13.03 cm)
Weight	4.1 lbs (1.86 kg)
Driver Complement	<ul style="list-style-type: none">• (1) 8" (20.32 cm) d (Round) Dynamic Balance aerated polypropylene cone and rubber surround - Mid/Woofer• (2) 0.75" (1.91 cm) d (Round) Dynamic Balance ring radiator tweeter - Tweeter
Grille Dimensions	11.125" (28.26 cm) diameter
Shape	Round
Dimensions	9.38" (23.83 cm) diameter
Total Frequency Response	30 Hz → 33,000 Hz
Nominal Impedance	8 ohms
Sensitivity 1 watt per 1 meter	88 dB
Lower and Upper -3dB Limits	45 Hz → 29,000 Hz
Recommended Amplifier Power Per Channel	10 watts → 125 watts
Audio Inputs	-
Speaker Inputs	(1) Pair of Push Connectors - Gold Plated